



**EMBENTION**

*Enabling drones  
to populate our skies*



**1x 4.8**

**AUTOPILOTS**

## **CONTROL SYSTEM FOR AUTONOMOUS VEHICLES**

Fully autonomous control for UAVs, UGVs, USVs and triparted eVTOLs.

High reliability and certification in compliance with DO178-C, DO254 and DO160-G aviation standards up to DAL B.

## **HIGH RELIABILITY CONTROL SYSTEM**



### **USER PROGRAMMABLE**

Model-based design tools enable custom programs and control logics.



### **CERTIFICATION**

Aircraft certification: DO178-C, DO254, DO160-G, ESS, ATR, STANAG, etc.



### **SENSE & AVOID**

Embedded ADS-B or Remote ID and support for external detection means.



**VERONTE  
AUTOPILOTS**

[www.embention.com](http://www.embention.com)

[sales@embention.com](mailto:sales@embention.com)

+34 965 115 421

## MAIN FEATURES

All Vehicles	Plane   Multi   Heli   Autogiro   VTOL   USV   +
100% Autonomous	Mission & payload   Assisted / manual / auto
Advanced Control	Adaptative   Curve-based   Fly-by-camera
Sense & Avoid	Radar   Lidar   Camera   ADS-B   Remote ID
All-in-one Box	Sensors   FTS   Comms   ADS-B or Remote ID
Internal Sensors	3x IMU   3x Magneto   2x Barometer   1x Pitot
Positioning	2x GNSS   RTK   GNSS Heading

## USER PROGRAMMABLE

Programs	Model based design   Customization   PID level
Phases	Takeoff   Landing   Cruise   Hover   Transition   +
Automations	Failsafe   Phase change   Operation   Payload
Navigation	Sensor mix   Kalman filter   External sensors
Pheripherals	Gimbal   ADS-B   Altimeter   Cameras   Others
Compatibility	Custom protocols   Mission computer

## I/O

Ports	16x PWM/GPIO   5x ADC
Buses	2xCAN   1xI2C   1xRS232   1xRS485   1xUART
Expandible	Veronte CEX   Up to 32 actuators

## COMMUNICATIONS



Internal LOS	2.4Ghz   100mW   Configuration   Tuning
Internal BLOS	LTE   Cloud communications   Worldwide
External	LOS   Satcom   4G/5G

## SAFETY & CERTIFICATION

Certification Ready	DO178C   DO254   DAL-B   DO160
Failsafe	Dissimilar supervisor   FTS
Protections	ESD, Overtemperature, Short Circuit, RP
Robust Manuf.	ATR, DDP & DoD   ESS & Calibration in all units

## GENERAL

Power Input	6.5 - 36VDC   Redundant power input
Power	5 - 15W
Temperature range	-40 to 60°C
Weight	198g   210g including ADS-B/Remote ID



[P006982] Veronte Autopilot 1x - w/o DAA V4.8  
[P006142] Veronte Autopilot 1x - Remote ID V4.8

[P006143] Veronte Autopilot 1x - ADS-B V4.8  
[P006365] Veronte Autopilot 1x - Target/Loitering V4.8