



# REDUNDANT FLIGHT **CONTROL SYSTEM**

Designed for the control of critical UAVs, eVTOLs and autonomous vehicles.

Includes 3 complete autopilot cores with DAL-B compliance for DO178-C, DO254 and DO160-G. Optional 4th core.

## **HIGH RELIABILITY CONTROL SYSTEM**



Create custom programs and control logics using model-based design.



**CERTIFICATION** 

DO178-C, DO254, DO160-G, ESS, ATR, STANAG ... for aircraft certification



**4X REDUNDANT** 

3 internal autopilot cores and 4th external core with no single point of failure.











## **MAIN FEATURES**

All Vehicles Plane | Multi | Heli | Autogiro | VTOL | USV | 100% Autonomous Mission & payload | Assisted / Manual / Auto

Onboard or remote joystick Fly-by-wire

**High Reliability** Full redundant | Fail operational

Sense & Avoid Radar | Lidar | Camera | ADS-B | Remote ID

**Internal Sensors** 9x IMU | 9x Magneto | 6x Barometer | 3x Pitot

6x GNSS | RTK | GNSS Heading **Positioning** 

Communications Internal LOS, LTE | External LOS, LTE, Satcom

## **USER PROGRAMABLE**

Model based design | Customization | PID level **Programs** Takeoff | Landing | Cruise | Hover | Transition | **Phases** Failsafe | Phase change | Operation | Payload **Automations** Navigation Sensor mix | Kalman filter | External sensors Gimbal | ADS-B | Altimeter | Cameras | Others Pheripherals

Compatibility Custom protocols | Mission computer

#### 1/0

PWM/GPIO | ADC Ports

CAN | I2C | RS232 | RS485 | UART **Buses** 

**Auxiliary** PWM | I2C | RS232 | RS485 | ADC | ARINC

Expandible Veronte CEX | Up to 32 actuators

## **SAFETY & CERTIFICATION**

3 Internal autopilot cores | 4th External Redundancy

Customizable Configurable voting logics Robustness No single point of failure

Certification DO178-C | DO254 | DAL-B | DO160-G

Failsafe Dissimilar supervisor | FTS

**Protections** ESD, overtemperature, short Circuit, RP

Robust Manuf. ATR, DDP & DoD | ESS & Calibration in all units

## **GENERAL**

6.5 - 36VDC | 17-47W | Redundant input **Power Input** 

Construction Anodized aluminium | IP67

Temperature -40 to 60°C

Weight 750g











